

## Strip-Brite 222 - Heavy Duty Paint Remover

### DESCRIPTION

Strip-Brite 222 is an acidic-type gel paint remover formulated to strip tough coatings from many surfaces, including aluminium. Strip-Brite 222 clings to vertical surfaces and to the underside of horizontal surfaces. Rinses-off easily at low pressure and forms a visible film during rinsing which aids in stripper removal. Strip-Brite 222 offers versatility, quick stripping speed and multi-layer paint removal.

### DIRECTIONS

Strip-Brite 222 should be used full strength at 65 - 85 °F. Apply a thick and even coat with non-atomizing spray or brush. Allow sufficient time for the paint to loosen and then agitate with a stiff bristle brush. Check if paint has been completely removed; if not apply a second thin layer of Strip-Brite 222. When stripping is complete, wash with cold or warm water at 50 psi or higher.

### CAUTION

Strip-Brite 222 contains Methylene Chloride and Acetic acid. Use only in well ventilated areas. Avoid ingestion, prolonged inhalation, and contact with skin, eyes and clothing. Use a face shield and solvent resistant clothing when handling or working with this product. Plexiglas and rubber should be protected from contact with Strip-Brite 222. Other surface materials may also be incompatible with this stripper; test a small area to ensure proper results.

### NOTICE

To our best knowledge, the information and recommendations contained herein are accurate and reliable. However, this information and our recommendations are furnished without warranty, expressed or implied. The manufacturer's sole obligation shall be to replace the portion of the product proven to be defective. The seller or manufacturer shall not be liable for any loss, damage or injury from the use or possession of this product.